

# Swimming Pool Lamps

Incandescent, gas-filled reflector lamps in spot, flood and wide flood versions specifically designed for swimming pools and underwater applications



*Ideal for swimming pools and underwater fixture applications using 12 or 120 volts*

► **Ideal for Applications Using 12 or 120 Volts**

- Swimming pools
- Waterfall lighting
- Fountain lighting
- Reflection pools

► **Hard, Shatter-Resistant Glass Withstands Thermal Shock and Vibration**

► **Specially Designed Filament Mounts for Ruggedness and Shock Resistance**

► **12-Volt Lamps Blend the Desired Feature of Safety from Electric Shock with Durability**

► **Available in G-30, PAR-56, R-20 and R-40, Depending on Wattage**

► **Single Coil or Coiled Coil Filament and Medium, Mogul or Multipurpose Type Bases**



# PHILIPS

**Philips Lighting Company**  
**200 Franklin Square Drive**  
**P.O. Box 6800**  
**Somerset, NJ 08875-6800**  
**1-800-555-0050**

A Division of Philips Electronics North America Corporation

Updated 7/04

P-2538-C

[www.philips.com](http://www.philips.com)

**Philips Lighting**  
**281 Hillmount Road**  
**Markham, Ontario**  
**Canada L6C 2S3**  
**1-800-555-0050**

A Division of Philips Electronics Ltd.

## Swimming Pool Lamps

Electrical, Technical and Ordering Data (Subject to change without notice)

Product Number	Ordering Code	Watts	Volts	Bulb	Base	Std. Pkg. Qty.	Description	Filament	MOL (In.)	Rated Average Life (Hrs.)	Approx. Initial Lumens
22135-8	100R20	100	120-130	R-20	■ Med.	12	Reflector Spot	C-9	3 1/8	2000	1000
33703-0	100R20/FL/S	100	12	R-20	■ Med.	60	Reflector Flood	C-6	3 1/8	2000	—
33710-5	300R/FL/I	300	12	R-40	■ Med.	24	★ Reflector Flood, IF	C-2V	6 3/8	2000	—
26084-4	300PAR56/WFL	300	12	PAR-56	† M.P.	8	★ Wide Flood	C-6	4 1/2	1000	6000
37442-1	300R/FL/I	300	120-130	R-40	■ Med.	24	Reflector Flood	CC-11	6 3/8	2000	2480
23551-5	300R/3FL	300	120	R-40	Mog.	24	★ Reflector Flood	CC-11	7 1/4	2000	3600
23557-2	300R/3FL	300	130	R-40	Mog.	24	★ Reflector Flood	CC-11	7 1/4	2000	3600
37443-9	400G/FL	400	120-130	G-30	Med.	60	Flood, Clear	C-7A	5 1/8	800	6645
31069-8	400R40/FL	400	120	R-40	■ Med.	24	Reflector Flood	C-7A	6 3/8	2000	—
37450-4	500R/3FL	500	120-130	R-40	Mog.	24	Reflector Flood, IF	CC-11	7 1/4	2000	—
33730-3	500R/3FL/2S	500	130	R-40	■ Med.	24	★ Reflector Flood, IF	C-7A	6 3/8	2000	—

■ Nickel plated brass base

★ Heat resisting glass bulb

† M.P. = Multipurpose screw terminal

